

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 December 2004 (23.12.2004)


PCT

(10) International Publication Number
WO 2004/111964 A1

- (51) International Patent Classification⁷: **G08B 21/02**, G01S 5/02
- (74) Agents: **SHERRARD-SMITH**, Hugh et al.; Appleyard Lees, 15 Clare Road, Halifax HX1 2HY (GB).
- (21) International Application Number: **PCT/GB2004/002464**
- (22) International Filing Date: 10 June 2004 (10.06.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0313649.6 13 June 2003 (13.06.2003) GB
- (71) Applicant (for all designated States except US): **SIGNATURE INDUSTRIES LIMITED** [GB/GB]; Tom Cribb Road, Thamesmead, London SE28 0BH (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **CLAYTON, Brian** [GB/GB]; Signature Industries Limited, Tom Cribb Road, Thamesmead, London SE28 0BH (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **ACTIVATION MECHANISM FOR A PERSONAL LOCATOR BEACON**



(57) Abstract: A key ring (160) is attached by a lanyard to part of an air craft. Upon the air crew ejecting a leash retains the pull pin (120) within the air craft to remove the pin from the housing (140). This activates a personal locator beacon. Removal of the pin (120) allows a plunger switch extending upwardly from the locator beacon to be released to activate the beacon.



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.